


N83624 Series High-accuracy Multi-channel Battery Simulator



Product Introduction

N83624 is a programmable battery simulator with low-power, multi-channel and high-accuracy, suitable for BMS/CMS test. It is highly integrated, single device with up to 24 channels. Each channel is isolated. Users can set the voltage & current for each channel on application software, which is easy to use and can meet the needs of multi-channel and multi-data. The software can also provide graphs, data analysis and report function. N83624 is equipped with high-definition color LCD screen, available for local operation.

Application Fields

- ▶ BMS test and CMS test
- ▶ Electric tools manufacturing test
- ▶ Consumer Electronics R&D and production, such as mobiles, tablets, earphones, etc.
- ▶ Other battery-operated products manufacturing test

Main Features

- ▶ Voltage range: 0-6V/0-15V
- ▶ Current range: 0-1A/0-3A/0-5A
- ▶ Single device with up to 24 channels, each channel isolated
- ▶ Fast communication response, within 10ms for all channels programming response
- ▶ Fast dynamic response, less than 100 μ s for load varying from 10% to 90% and voltage recovering within 50mV
- ▶ Remote sense for high accuracy
- ▶ Professional application software, with data analysis and report
- ▶ High-definition color LCD screen, available for local operation
- ▶ Standard 19-inch 3U, available for rack installation
- ▶ LAN port and RS232 interface; dual LAN ports, convenient for cascade application

Ultra-high accuracy


N83624 current resolution is as low as 0.1 μ A. Ultra-high accuracy, ultra-low ripple and noise index make N83624 an ideal choice for battery simulation application. The ultra-high accuracy of N83624 output and measurement can be directly used in product calibration and test, eliminating the use of external high-accuracy measuring instruments and saving cost for users.



▲ N83624 Load Mode

Ultra-high integration

N83624 integrates up to 24 channels that can be connected in series mode in 19-inch 3U size, providing a compact solution for ATE test systems in BMS, CMS and similar large-scale high-density production sites.




▲ 24 Channels in 3U


Battery simulation suitable for BMS chips test of various specifications

N83624 series battery simulators have multiple functions and features, supporting Source, All CH, Charge, SOC Test, SEQ, Graph, etc.

One device can achieve multiple uses, streamline test equipment and optimize test procedures. N83624's internal circuit is optimized for different chips, which can be adapted to test BMS chips of various specifications.




▲ Source




▲ All CH




▲ SOC Test



▲ SEQ




▲ Graph




▲ System

Fast dynamic response

N83624 series has fast dynamic response capability. The response time of load varying from 10% to 90% and voltage recovering within 50mV is less than 100 μ s, which can ensure the rising waveform of voltage or current is high-speed and without overshoot, and provide stable power for the DUT. This feature meets the test demand for strictly regulated power products.




▲ N83624 Full-load Rise Time (7.65µs)



▲ N83624 Full-load Fall Time (21.5µs)


LAN port and RS232 interface, easy for cascade application

N86324 series supports LAN port and RS232 interface. LAN port is designed with dual ports, which can be used for remote control and also for cascade application.



- ① AC power socket
- ② LAN port
- ③ RS232 interface
- ④ Channel interface

Product Dimension



Technical Data Sheet

Model	N83624-06-01	N83624-06-03	N83624-06-05	N83624-15-01				
Current	1A/CH	3A/CH	5A/CH	1A/CH				
Voltage	6V/CH	6V/CH	6V/CH	15V/CH				
Power	6W/CH	18W/CH	30W/CH	15W/CH				
Channels	24CH	24CH	24CH	24CH				
CV Mode								
Range	0-6V			0-15V				
Setting Resolution	0.1mV			0.3mV				
Setting Accuracy (23±5℃)	0.01%+1mV			0.01%+3mV				
Readback Resolution	0.1mV			0.3mV				
Readback Accuracy (23±5℃)	0.01%+1mV			0.01%+3mV				
Temperature Coefficient (0~40℃)	20ppm/℃							
Long-term Stability	80ppm/1000h							
Dynamic Characteristics								
Voltage Rise Time	<20μs (no load) (10%-90%F.S. Variation Time)							
Voltage Rise Time	<20μs (pure resistive full load) (10%-90%F.S. Variation Time)							
Voltage Fall Time	<3ms (no load) (10%-90%F.S. Variation Time)							
Voltage Fall Time	<100μs (pure resistive full load) (10%-90%F.S. Variation Time)							
Transient Voltage Drop ¹	200mV			400mV				
Transient Recovery Time ²	<100μs			<200μs				
Current Measurement								
Range	0-1A	0-1mA	0-3A	0-1mA	0-5A	0-1mA	0-1A	0-1mA
Readback Resolution	0.1mA	0.1μA	0.3mA	0.1μA	0.5mA	0.1μA	0.1mA	0.1μA
Readback Accuracy (23±5℃)	1mA+2d	1μA+2d	3mA+2d	1μA+2d	5mA+2d	1μA+2d	1mA+2d	1μA+2d
Temperature Coefficient (0~40℃)	30ppm/℃							
Long-term Stability	100ppm/1000h							
Current Protection Limit								
Setting Value	0-1A	0-1mA	0-3A	0-1mA	0-5A	0-1mA	0-1A	0-1mA
Setting Resolution	0.1mA	0.1μA	0.3mA	0.1μA	0.5mA	0.1μA	0.1mA	0.1μA
Setting Accuracy (23±5℃)	0.3%F.S.							
Temperature Coefficient (0~40℃)	30ppm/℃							
Long-term Stability	100ppm/1000h							
Others								
Load Regulation	0.1mV							
Isolation (Output to ground)	1000VDC							
Isolation (Inter-channel)	500VDC							
Communication Response Time	All channels <10ms							
Interface	LAN/RS232							
AC Input	Single phase, 220V AC±10%, current <1A, frequency 47Hz-63Hz							
Temperature	Operating temperature: 0℃-40℃, storage temperature: -20℃~60℃							
Operating Environment	Altitude <2000m, relative humidity: 5%-90%RH(non-condensing), atmospheric pressure: 80-110kPa							
Net Weight	Approx. 17kg							
Dimension	3U, 132.5(H)*482.0(W)*559.0(D)mm							

Note 1: Load varies from 10% to 90% by full voltage output.

Note 2: Load varies from 10% to 90% by full voltage output, with voltage recovering within 50mV of previous voltage.

Note 3: For other specifications, please contact NGI.