



STARBOND 870

◎ PROPERTIES

- Main component : CR Synthetic Rubber
- Appearance : Yellowish transparent viscous liquid
- Viscosity : 11,000±1,000 CPS
- Solid content : 23±1
- Shelf life : 6 months
- Validity : 12months, Avoid direct sunlight and store in a cold and dry place. (5~25°C)

◎ COMPONENTS

| Division | STARBOND 870 |
|---------------------|--------------|
| CR Synthetic Rubber | 10 |
| Resin | 14 |
| Solvent | 76 |

◎ COMPONENTS

- Fast drying, long tack, excellent brush workability and adhesion.
- Widely used in rubber, leather, wood, plastic, shoes and metal.
- Pot life is long, so it allowed to adhere even after 5 to 6 hours of application.

◎ METHOD OF USE

- The surfaces to be adhered shall be completely free of moisture, dust, oil and other substances.
(Drying after sweeping, solvent washing, buffing and cleaning.)
- Apply adhesive on both sides of the adherend and compress it within the open time.
(sticky when touching).
- The super absorbent material shall be fully applied for more than two times before bonding.
- The adhesion is different according to the amount of application, the application method, the compression pressure and compression time.



◎ PRECAUTIONS

- Avoid contact with eyes, respiratory system and skin when handling.
Wear protective equipment (mask, gloves). Be sure to ventilate the place of handling and be careful about static electricity and fire.
- Don't smell it. After use, seal any excess adhesive and store in a well ventilated area.
- Do not use for any other purpose, please keep out of the reach of children.
- Storage at room temperature. Stored at below 0 ° C it may be frozen.
- For further information, refer to MSDS.